

10 TOP

FEATURES OF

element
screens



1. The strength of Elements Screen's motor tube coupled with the extruded hood allows for installations up to 24' wide without sagging.
2. Side tracks are only 2 inches wide and $\frac{5}{8}$ inches thick, enabling the frame to blend unobtrusively in with the building's façade.
3. MaestroShield has the only extruded hood on the market. Our extruded hood is 66% thicker than sheet metal hoods, making it resistant to denting in shipping and handling, and impact resistant when installed. Our side caps, featuring deep galvanized steel threaded inserts for attaching the mounting plates, are 87% thicker than standard universal side caps.
4. The 5½ inch hood assembly and small profile side rails are light weight and allow for **quick and easy installation.**
5. The 2-piece side track enables you to hide the mounting screws for a cleaner, more attractive appearance.
6. The contoured bottom bar, designed to retract into the hood assembly, accommodates a weighted steel bar insert which assists in keeping the screen taut and operating smoothly.
7. Zipper system allows screen to be tensioned and still run smoothly without ever needing adjustment.
8. Plastic entry guides provide for clean entry of zipper into side rails, assuring smooth operation for the lifetime of the assembly. **PLUS**, the guide allows for the bottom bar to retract almost entirely into hood.
9. Heavy duty idler system allows for smooth and quiet operation. Spring-loaded idler allows for simple installation of motor tube assembly, and for removal of assembly quick and easy if necessary.
10. Industry-leading warranties: **10-year** warranty on powder coating (1-year in coastal regions within 1 mile of saltwater coastline); **5-year** full replacement warranty on tubular motors (3-year for Smart Series motors with internal receiver); **2-year** full replacement warranty on electronics and components.



www.maestroshield.com
Phone: 239.596.8883 | Fax: 239.596.8823